

Automated Guided Vehicle

AGV X1



AGV X1

- · Forward and reverse drive
- · Differential drive enables turning on the spot
- Wear-free charging during operation due to inductive charging system
- Scalable battery capacity with LiFePO4 batteries to adapt to process requirements
- 7" touch user interface for easy interaction
- Agent-based system that enables communication between the AGVs and their environment
- Electric lifting pin for lifting payloads up to 1500 kg
- Driving speeds from 0.02 m/s up to 1.6 m/s
- Navigation: track guided magnetic or virtual track
- Hybrid localization: grid-sensor, contour detection, camera, RFID, odometry and magnetic track
- · Safety laser scanner in each direction of travel



ELECTRIC DATA	
Operating voltage AGV [V]	24 DC
Charging time with inductive charger (for 1/2/3 batteries) (min)	30 40 60*
Capacity (for 1/2/3 batteries) (Ah)	21 42 63

OPERATIONAL DATA	
Temperature range (°C)	+5 to +35
Positioning accuracy (mm)	+/- 5*
Min. turning radius (m)	1.0
Max. speed with/without payload (m/s)	1.0 1.6*
Continous driving without payload (for 1/2/3 batteries) (h)	4 8 12*

MECHANICAL DATA	
Steel/technopolymers	
840 820 340**	
215	
1500*	

^{*}environment-dependent




^{*}without optional accessories



X1 Turn Table version

Dimensions



Dimensions in millimeters





WAMECH P.S.A.

Torowa 3T Street
30-435 Cracow
VAT ID PL6790026622